

Jazzy[®]

SELECT TRAVELLER

The Jazzy Select[®] Traveller delivers high performance maneuverability and efficiency in a compact, stylish package. A powerful PG GC programmable controller, in-line motors, and enhanced battery size are just a few of the features that make the Jazzy Select Traveller an excellent overall value.



Jazzy Select[®] Traveller
shown in Red

(US) 800-800-8586 • (Canada) 888-570-1113
Visit us on the web: www.pridemobility.com

Pride[®]
Mobility Products Corp.

SPECIFICATIONS

Weight capacity	300 lbs.
Maximum speed	Up to 3.5 mph
Ground clearance	1.75"
Turning radius	22.75"
Overall length	27.75"
Overall width	21.5"
Drive Wheels	8"
Front anti-tips	5" solid
Rear casters	3" solid
Suspension	Limited
Drive train	Two-motor, in-line, rear-wheel drive
Braking system	Intelligent braking (electronic, regenerative disc brakes)
Standard electronics	40 amp, PG GC controller
Specialty controls	No
Battery charger	Off-board, 3 amp (standard)
Per-charge range	Up to 15 miles
Battery requirements	(2) 12 volt, deep cycle
Battery size	U-1
Battery weight	24.5 lbs. each
Base weight	70 lbs.
Standard seat weight	30 lbs.
Max. seat dimensions	18" x 16"
Warranty	5-year limited warranty on frame; 1-year limited warranty on electronics; 1-year limited warranty on drive motors

COLOR CHOICES



Red



Blue

MODELS

Jazzy Select-C

FEATURES

- U-1 batteries for greater per charge range
- In-line motor technology for increased torque and efficiency
- Tight turning radius of 22.75" for tight space maneuverability
- Solid tires for worry free ride
- 40 amp PG GC controller
- 300 lbs. weight capacity
- 21.5" overall width
- 3 amp off-board charger
- Full length padded armrests

OPTIONS

- Weather cover
- Cup holder
- Rear basket

RECOMMENDED LIFTS

Pride SilverStar®
Lifts & Ramps 

- Backpacker® Plus
- Backpacker® MV
- Silver Boom 300
- Full Platform



Pride®
Mobility Products Corp.

(US) 800-800-8586 ▪ (Canada) 888-570-1113
Visit us on the web: www.pridemobility.com

The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%.